

MATERIAL SAFETY DATA SHEET

MEDICAL EMERGENCY ONLY, 24 HOUR SERVICE: 1-800-535-5053

PRODUCT : NU SOFT 5 GAL DR *

1109NE

Sanolite Corporation

26 Papetti Plaza Elizabeth NJ 07207-0818 (800) 221-0806

1.0 IDENTIFICATION

- | | | |
|-----|---------------|---------------------|
| 1.1 | PRODUCT NAME: | NU SOFT 5 GAL DR * |
| 1.2 | PRODUCT TYPE: | LAUNDRY SOFT,LIQUID |
-

2.0 HAZARDOUS COMPONENTS

- | | | |
|-----|---|---|
| 2.1 | : | HYDROXYACETIC ACID C.A.S. NO. 79-14-1 |
| 2.1 | : | METHYL BIS(TALLOW AMIDO ETHYL)2-HYDROXYETHYL
AMMO- NIUM METHYL SULFATE,ETHOXYLATED C.A.S.
#68410-69-5 |

This product contains no other component considered hazardous according to the criteria of 29 CFR 1910.1200.

3.0 PHYSICAL DATA

- | | | |
|-----|----------------------|---|
| 3.1 | APPEARANCE AND ODOR: | LIGHT BLUE-GREEN VISCOUS LIQUID; PLEASANT ODOR. |
| 3.2 | SOLUBILITY IN WATER: | COMPLETE |
| 3.3 | PH:: | 1.0-2.5 |
| 3.4 | BOILING POINT:: | 212 DEGR.F |
-

4.0 FIRE & EXPLOSION DATA

- | | | |
|-----|-----------------------------|---|
| 4.1 | FIREFIGHTING METHODS: | PRODUCT DOES NOT SUPPORT COMBUSTION. |
| 4.2 | FIRE AND EXPLOSION HAZARDS: | CONTACT WITH ACTIVE METALS MAY PRODUCE
FLAMMABLE HYDROGEN GAS. |
-

5.0 REACTIVITY DATA

- | | | |
|-----|---------------------------|---|
| 5.1 | STABILITY: | STABLE UNDER NORMAL CONDITIONS OF HANDLING. |
| 5.2 | CONDITIONS TO AVOID: | EXCESSIVE HEAT. |
| 5.3 | INCOMPATIBILITY: | ACTIVE METALS, ALKALINE SUBSTANCES, STRONG
OXIDIZING AGENTS. |
| 5.4 | HAZ.DECOMP.PROD: | NONE |
| 5.5 | HAZARDOUS POLYMERIZATION: | WILL NOT OCCUR |
-

6.0 SPILL OR LEAK PROCEDURES/ USE PROPER PROTECTIVE EQUIPMENT

- | | | |
|-----|----------|--|
| 6.1 | CLEANUP: | ABSORB WITH INERT MATERIAL AND PLACE IN A
CONTAINER FOR PROPER DISPOSAL.FLUSH SPILL AREA
WITH WATER. |
|-----|----------|--|

MATERIAL SAFETY DATA SHEET

MEDICAL EMERGENCY ONLY, 24 HOUR SERVICE: 1-800-535-5053

PRODUCT : NU SOFT 5 GAL DR *

1109NE

Sanolite Corporation

26 Papetti Plaza Elizabeth NJ 07207-0818 (800) 221-0806

6.0 SPILL OR LEAK PROCEDURES/ USE PROPER PROTECTIVE EQUIPMENT

6.2 WASTE DISPOSAL: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

7.0 HEALTH HAZARD DATA

7.1 A EYES: MAY CAUSE IRRITATION.
 7.1 B SKIN: IRRITATING TO SKIN.
 7.1 C IF SWALLOWED: INJURIOUS IF TAKEN INTERNALLY.
 7.1 D IF INHALED: MAY CAUSE IRRITATION OF MUCOUS MEMBRANES.

8.0 FIRST AID

8.1 EYES: IMMEDIATELY FLUSH WITH PLENTY OF COOL RUNNING WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.
 8.2 SKIN: WASH OFF WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, OBTAIN MEDICAL ATTENTION.
 8.3 IF SWALLOWED: DRINK A LARGE QUANTITY OF WATER OR MILK. DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.
 8.4 IF INHALED: REMOVE TO FRESH AIR
CALL A POISON CONTROL CENTER OR PHYSICIAN IMMEDIATELY

9.0 SPECIAL PROTECTION INFORMATION

9.2 SKIN:: RUBBER GLOVES - PROTECTIVE CUFF OR GAUNTLET TYPE PREFERRED, IF HANDLING CONCENTRATE.
 9.3 EYE PROTECTION:: SPLASHPROOF GLASSES, GOGGLES OR FACE SHIELD.
 9.5 VENTILATION:: LOCAL EXHAUST

10.0

10.0 PROTECT EYES AND SKIN FROM CONTACT. KEEP AWAY FROM ALKALINE MATERIALS.
 10.1 D.O.T. CLASS: COMPOUND, CLEANING LIQUID, N.O.I.B.N.
 10.3 OTHER PRECAUTIONS: FOR INDUSTRIAL USE ONLY
 10.4 DATE APPROVED: 11/06/2006

UNK = Unknown at this time PEL = Permissible Exposure Limit
 TLV = Threshold Limit Value STEL = Short Term Exposure Limit
 C = Ceiling Limit, Not To Be Exceeded

MATERIAL SAFETY DATA SHEET

MEDICAL EMERGENCY ONLY, 24 HOUR SERVICE: 1-800-535-5053

PRODUCT : NU SOFT 5 GAL DR *

1109NE

Sanolite Corporation
26 Papetti Plaza Elizabeth NJ 07207-0818 (800) 221-0806

KEEP OUT OF REACH OF CHILDREN

The above information is believed to be correct with respect to the formula used to manufacture the product. As data, standards, and regulations change, and conditions of use and handling are beyond our control, **NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.**

UNK = Unknown at this time PEL = Permissible Exposure Limit
TLV = Threshold Limit Value STEL = Short Term Exposure Limit
C = Ceiling Limit, Not To Be Exceeded