



Product Information Sheet

Daycon Products Company, Inc. 16001 Trade Zone Avenue, Upper Marlboro, MD 20774
Local: (301) 218-1000 Toll Free: (800) 394-0019 Fax (301) 218-7191

This sheet is not a Material Safety Data Sheet (M.S.D.S.), nor does it satisfy the requirements to have one. All information on this sheet is believed to be accurate, but no warranty is expressed or implied. The product described herein is for use only by trained, professional, cleaning personnel.

GRAFFITI-B-GONE GEL

Fast-Acting Graffiti Remover

Description:

Graffiti-B-Gone Gel was formulated to aid in the quick removal of unsightly graffiti. It is a highly-alkali gel which may be applied to vertical surfaces to loosen any graffiti. Graffiti-B-Gone Gel is methylene chloride free. It removes most paint and ink, and will remove crayon, lipstick, and magic marker. It is fast-acting and comes ready-to-use. Graffiti-B-Gone Gel is completely biodegradable.

Benefits:

- Fast acting
- Ready-to-use
- Completely biodegradable
- Gelled formula for increased dwell time
- Methylene Chloride Free
- Removes paint, ink, crayon, lipstick, and magic markers
- For use on masonry surfaces

Specifications:

Appearance:	Clear Gel
Color:	Brown
Odor:	Detergent
Use Dilution:	As is
Storage Stability:	Two years minimum in closed container
Protective Clothing:	See Safety Data Sheet (SDS)
VOC's, % as is:	18
Product Conformance:	Manufactured by an ISO 9001:2008 registered company.

Comment:

Graffiti Remover is an ideal product to use in conjunction with a pressure washer or manual agitation. Do not use on aluminum.

Directions:

Apply Graffiti-B-Gone Gel with a sponge or brush to the surface that has graffiti or paint that needs to be removed. Allow to remain in contact for 1-3 minutes and then scrub with an abrasive pad and then wipe or rinse off. For best results, when working on brick, concrete, or cinder blocks, the use of a pressure washer will remove any shadow left behind. Graffiti-B-Gone Gel may also be used as a paint and varnish stripper during preparation of wood floors. When working on wood floors, apply the product using a toy broom, allow it to sit 5 minutes, and then remove using a steel wool pad on a low speed scrubber.

Product Disposal:

Dispose of in accordance with local, state, and federal regulations. It is recommended that the high density polyethylene container and any corrugated packaging be recycled.

Packed:

Packaging/Description	Item Code
Gallon (4 per case)	GRAFGELGAL

Date:

May 2, 2013