



## Product Information Sheet

Daycon Products Company, Inc. 16001 Trade Zone Avenue, Upper Marlboro, MD 20774  
Local: (301) 218-1000 Toll Free: (800) 394-0019 Fax (301) 218-7191

This sheet is not a Material Safety Data Sheet (M.S.D.S.), nor does it satisfy the requirements to have one. All information on this sheet is believed to be accurate, but no warranty is expressed or implied. The product described herein is for use only by trained, professional, cleaning personnel.

# Aqua-Coat II

## High Gloss Finisher and Sealer

**Description:** An aqueous colloidal urethane emulsion for sealing and finishing wood floors. Aqua-Coat II exhibits high gloss, excellent film clarity, scuff and scratch resistance, and recoatability. It can be applied by short nap applicator, a weighted T-Bar applicator, or brush. It dries in 40 minutes to 1 hour. Aqua Coat II is based on an aliphatic polyurethane, so it will not yellow. Applicators can be cleaned with water. It is detergent resistant and will not spot during cleaning. Aqua Coat is the ideal coating for gyms, racquetball courts, stores, and residential flooring.

**Benefits:**

- Surface can be burnished to restore or improve gloss
- Bare wood surfaces can be sealed, finished, and put in walking service in 12 hours. Gymnasiums and racquetball courts should not be put in full service for 5-7 days.
- Safe and pleasant to use
- Non-flammable and no solvent fumes or odors
- Low VOC's

**Specifications:**

Appearance	Translucent liquid
Color	Light white
Odor	Mild odor
Specific Gravity	1.055 ± 0.003 @ 20°C
Active Ingredients	31.3% ± 0.5%
Total Solids	25% ± 0.1%
Flash Point	None
pH: as is	8.5 ± 0.5
Use Dilution	As is
Storage Stability	Two year minimum in sealed containers
Protective Clothing:	None required
Leveling	Excellent
Coverage	800 -1000 sq ft per. gallon on bare wood 1000 - 1500 square feet per gallon for additional coats.
VOC Content:	Less than 5% by weight

**Comments:** Product is easily removed by using sanding discs and a low speed floor machine. If you recoat before 3 hours, you do not have to re-screen the floor. When applying additional coats after the previous coat has dried for more than 3 hours, lightly screen the floor prior to applying Aqua Coat II

**Packed:** 5 Gallon Pail

**UPC-A Code:** 5 GAL: 704474051000

**Interleaved 2 of 5:**

**Code:** 801251

**Date:** September 11, 2009