

MATERIAL SAFETY DATA SHEET

A15870

ITEM NUMBER: 870 - VANDALISM MARK & STAIN REMOVER

Version 2 EFFECTIVE DATE: 3/3/00 SUPERCEDES: 8/20/97

IDENTITY (As Used On Label and List All Purpose Degreaser and Vandal Remover

EMERGENCY MEDICAL Telephone# 1-800-228-5635 X 009 (24 Hrs)

Outside of the U.S.A. Call 651-632-9275

PRODUCT HAZARD RATINGS (HMIS): Health = 2, Fire = 2, Reactivity = 0, Protective Equipment = B

(Rating Legend: 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal)

SECTION I

Daycon Products Company Inc.

16001 Trade Zone Avenue

Upper Marlboro, MD 20774-8795

TELEPHONE NUMBER FOR INFORMATION : 1-301/218-1000

DATE PRINTED : 8/18/00 NAME OF PREPARER : Ron Cepa

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Chemical Names (LD50-Oral Rat)	SEC 313	Exposure Limits TLV/TWA	SARA Title III PEL	ACGIH	OSHA	% By Wt.
-----------------------------------	---------	----------------------------	-----------------------	-------	------	----------

Dichloromethane (CAS# 75-09-2)		1500/2400mg/kg	YES	50ppm	25ppm	43.0
Tetrchloroethylene (CAS# 127-18-4)		10g/kg (skin-rab.)	YES	50	100	10.0
Toluene (CAS# 108-88-3)		5g/kg (oral-rab.)	YES	50	200	15.0
Nonylphenol Ethoxylate (CAS# 9016-45-9)		4000mg/kg	-	NE	NE	1.5
Liquified Petroleum Gas (CAS# 68476-85-7)		NE	-	1000	1000	25-30

\*Unidentified ingredients are not considered hazardous under the Federal Hazard Communication Standard.

Components Listed As A Suspected Carcinogen: Methylene chloride is listed as an animal carcinogen by NTP, perchloroethylene - IARC & NTP. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

SECTION III - PHYSICAL CHARACTERISTICS

Boiling Point: NA Vapor Pressure (psig): 90@130F Specific Gravity (H2O=1): <1  
Solubility/Water: Negligible Vapor Density (AIR=1): >1 Evaporation Rate (Ether=1): <1  
Appearance and Odor: Heavy, coarse wet spray, strong methylene chloride and toluene odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Aerosol Flammability: This product is considered to be flammable as described in 16CFR 1500.45.

Flammable Limits - % Volume In Air (Propellant): LEL: 1.8 UEL: 9.2

Extinguishing Media: Carbon dioxide, foam and/or dry chemical may be used.

Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up.

Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.

Unusual Fire and Explosion Hazards: At elevated temperatures (over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.

SECTION V - REACTIVITY DATA

Stability: Stable Hazardous Polymerization: NA

Incompatibility (Materials to Avoid): Oxidizing agents, heat and open flame.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, hydrogen chloride, phosgene and additional toxic chemicals may be formed in small amounts.

Conditions to Avoid: Do not store above 54C-130F. Keep away from heat, direct sunlight, open flames or sparks. Dropping of containers may cause bursting.

